

MZ02 - MZE02


HYDRAULIC MOTORS

C	A	B	C	D	E	N
	mm[in]	mm[in]	mm[in]	mm[in]	mm[in]	mm[in]
1 1 1 0 1 2 3 4	Ø 175.7 [6.92 dia.]	Ø 225 [8.86 dia.]	Ø 265 [10.43 dia.]	253.45 [9.97]	Ø 334 [13.15 dia.]	Ø 24 [0.94 dia.]
1 2 1 0 1 2 3 4	Ø 220.7 [8.69 dia.]	Ø 275 [10.83 dia.]	Ø 314 [12.36 dia.]	253.25 [9.97]	Ø 291 [11.46 dia.]	Ø 22 [0.87 dia.]
1 7 1 0 1 2 3 4	Ø 220.7 [8.69 dia.]	Ø 275 [10.83 dia.]	Ø 314 [12.36 dia.]	253.25 [9.97]	Ø 334 [13.15 dia.]	Ø 22 [0.87 dia.]
1 3 1 0 1 2 3 4	Ø 175.7 [6.92 dia.]	Ø 225 [8.86 dia.]	Ø 276 [10.87 dia.]	208.75 [8.22]	Ø 334 [13.15 dia.]	Ø 24 [0.94 dia.]
1 4 1 0 1 2 3 4	Ø 220.7 [8.69 dia.]	Ø 254 [10.00 dia.]	Ø 285 [11.22 dia.]	163.2 [6.43]	Ø 334 [13.15 dia.]	Ø 17.5 [0.69 dia.]
1 1 1 0 1 2 3 4	Ø 175.7 [6.92 dia.]	Ø 225 [8.86 dia.]	Ø 265 [10.43 dia.]	253.45 [9.97]	Ø 334 [13.15 dia.]	Ø 24 [0.94 dia.]
1 2 1 0 1 2 3 4	Ø 220.7 [8.69 dia.]	Ø 275 [10.83 dia.]	Ø 314 [12.36 dia.]	253.25 [9.97]	Ø 291 [11.46 dia.]	Ø 22 [0.87 dia.]
1 7 1 0 1 2 3 4	Ø 220.7 [8.69 dia.]	Ø 275 [10.83 dia.]	Ø 314 [12.36 dia.]	253.25 [9.97]	Ø 334 [13.15 dia.]	Ø 22 [0.87 dia.]
1 3 1 0 1 2 3 4	Ø 175.7 [6.92 dia.]	Ø 225 [8.86 dia.]	Ø 276 [10.87 dia.]	208.75 [8.22]	Ø 334 [13.15 dia.]	Ø 24 [0.94 dia.]
1 4 1 0 1 2 3 4	Ø 220.7 [8.69 dia.]	Ø 254 [10.00 dia.]	Ø 285 [11.22 dia.]	163.2 [6.43]	Ø 334 [13.15 dia.]	Ø 17.5 [0.69 dia.]
1 2 1 0 1 2 3 4	Ø 220.7 [8.69 dia.]	Ø 275 [10.83 dia.]	Ø 314 [12.36 dia.]	253.25 [9.97]	Ø 291 [11.46 dia.]	Ø 22 [0.87 dia.]
1 7 1 0 1 2 3 4	Ø 220.7 [8.69 dia.]	Ø 275 [10.83 dia.]	Ø 314 [12.36 dia.]	253.25 [9.97]	Ø 334 [13.15 dia.]	Ø 22 [0.87 dia.]
1 3 1 0 1 2 3 4	Ø 175.7 [6.92 dia.]	Ø 225 [8.86 dia.]	Ø 276 [10.87 dia.]	208.75 [8.22]	Ø 334 [13.15 dia.]	Ø 24 [0.94 dia.]


T E C H N I C A L C A T A L O G



OVERVIEW



Motor inertia = 0.01 kg.m²
 Noise emissions = 60 dBA




	C	① cm ³ /rev [cu.in/rev.]	Theoretical torque		Max.power ① kW [HP]	Max. speed ① rev/min[RPM]	Max. pressure bar [PSI]
			at 100 bar Nm	at 1000 PSI [lb.ft]			
Cams with equal lobes	MZ02	0	213 [13.0]	339 [172]	18 [24]	470*	260 [3 771]
		1	235 [14.3]	374 [190]		430*	
		2	255 [15.6]	405 [206]		395*	
	MZE02	0	332 [20.2]	528 [268]	22 [30]	265*	260 [3 771]
		1	364 [22.2]	579 [294]		245*	
		2	398 [24.3]	633 [322]		225*	

* See option "M" for higher speed or lower charge pressure.

① First displacement



CONTENT



MODEL CODE 4 →

Model code

CHARACTERISTICS 7 →

Dimensions for standard 1-displacement motor	7
Pinion characteristics	8
	8

Characteristics

VALVING SYSTEMS 11 →

Hydraulic connections	11
Valves description	12

Valving systems

BRAKES 13 →

Rear brake	13
Automatic electrical de-braking valve	14

Brake

INSTALLATION 15 →

Hydraulic motor setting	15
Customer's chassis recommendations	15


Installation

OPTIONS 17 →

Options



MODEL



C1
Cam ring type

		1 displacement	
		cm ³ /rev. [cu.in/rev.]	
Cams with equal lobes	MZ02	213 [13.0]	0
		235 [14.3]	1
		255 [15.6]	2
MZE02		332 [20.2]	0
		364 [22.2]	1
		398 [24.3]	2

D1
Valves

Check valve	Pressure relief valve	Pressure relief valve with dynamic shockless	
Yes	Yes	No	A
Yes	No	Yes	B

D2
Pressure relief valve setting

Pressure settings and Dynamic shockless timing will be precisely determined based on machine design.
(see possible settings on page 12)

D3
Connection type

UNF (SAE) ISO 11926-1	A
GAZ (BSPP) JIS B2351	F

F1
Rear brake
mini./max. torque (N.m [lb.ft])


1 480 [1 092] / 1 830 [1 350]	F
890 [656] / 1100 [811]	J

F2
Debraking valve

Without debraking valve	1
Automatic electrical debraking valve	3



CODE





Methodology :

This document is intended for manufacturers of machines that incorporate Poclain Hydraulics products. It describes the technical characteristics of Poclain Hydraulics products and specifies installation conditions that will ensure optimum operation. This document includes important comments concerning safety. They are indicated in the following way:



Safety comment.

This document also includes essential operating instructions for the product and general information. These are indicated in the following way:



Essential instructions.



General information .



Information on the model number.Information on the model code.



Weight of component without oil.



Volume of oil.



Units.



Tightening torque.



Screws.



Information intended for Poclain-Hydraulics personnel.


The views in this document are created using metric standards.
The dimensional data is given in mm and in inches (inches are between brackets and italic)






CHARACTERISTICS


Dimensions for standard 1-displacement motor



8 Ear fixation 6 x Ø 16




9 Ear fixation 8 x Ø 14




* see dimensions in section "Pinion characteristics", page 8



Pinion characteristics




0




Norm	NF ISO 53
Module	6
Number of teeth	14
Pitch diameter	84 mm [3.31 inch]
Pressure angle	20°

1





Norm	NF ISO 53
Module	5
Number of teeth	17
Pitch diameter	85 mm [3.35 inch]
Pressure angle	20°


2



Norm	NF ISO 53
Module	5
Number of teeth	14
Pitch diameter	70 mm [2.76 inch]
Pressure angle	20°




Norm	NF ISO 53
Module	4,5
Number of teeth	11
Pitch diameter	49,5 mm [1.95 inch]
Pressure angle	20°



Norm	NF ISO 53
Module	6
Number of teeth	11
Pitch diameter	66 mm [2.60 inch]
Pressure angle	20°

Treated shafts

Heat treatment is applied on the whole surface of all shafts.



Model code

Characteristics

Valving systems

Brake

Installation



Options





VALVING SYSTEMS

Hydraulic connections



	Standards	Power supply	Case drain	Control of parking brake	Charge pressure
A	UNF (SAE)	A-B	1	F	T
F	GAZ (BSPP)	3/4"-16 UNF 3/8"	3/4"-16 UNF 3/8"	9/16"-18 UNF 1/4"	3/4"-16 UNF 3/8"

Max. pressures	MZ MZE bar [PSI]	260 [3 771] 260 [3 771]	2.5 [36]	35 [508]	260 [3 771]
Instantaneous pressure peaks resistance			15 [218]		




You are strongly advised to use the fluids specified in brochure "Installation guide" N° 801478197L.



To find the connections' tightening torques, see the brochure "Installation guide" N° 801478197L.




Valves description




Check valve

The check valve allows to compensate for leakages to prevent cavitation.




Flow rate l/min [GPM]	Operating pressure bar [PSI]	Cracking pressure bar [PSI]	Temperature range °C [°F]	Viscosity range mm ² /s	Filtration NAS 1638
100 [26.4]	350 [5 076]	0,5 [7.2]	-20 to +70 [-4 to 158]	15 to 380	8



Pressure relief valve

The pressure relief valve limits the pressure in the high pressure lines of the hydraulic motor.




Pressure relief valve with dynamic shockless

The pressure relief valve with dynamic shockless:

- limits the pressure in the high pressure lines of the hydraulic motor.
- allows the absorption of the pressure peacks.

Valve characteristics:


- Max. flow: 60l/min [15.85 gal/min]
- Shockless time: from 0,05 to 0,3 s
- Max. pressure setting: 260 bar [3771 PSI]




Other valve sizes are available. Consult your Poclair Hydraulics application engineer for further information.



BRAKES



Rear brake



Brake principle

This is a multidisc brake which functions through the absence of pressure. The spring exerts a force on the piston, which acts on the fixed and mobile discs, and thus immobilizes the shaft. The braking torque decreases in linear proportion to the brake release pressure.

	F			F		
	1	2	3	1	2	3
	F		0	J		0
Parking brake torque at 0 bars on housing	Max.	1 830 Nm [1 350 lb.ft]	1 100 Nm [810 lb.ft]			
	Mini.	1 480 Nm [1 090 lb.ft]	890 Nm [660 lb.ft]			
Min. brake release pressure		12 bar [174 PSI]	12 bar [174 PSI]			
Max. brake release pressure		35 bar [508 PSI]	35 bar [508 PSI]			
Volume for brake release		19 cm ³ [1,2 cu.in]	19 cm ³ [1,2 cu.in]			

Do not run-in the multidisc brakes.

Your duty cycles and especially brake cycles must be validated by your Poclain Hydraulics application engineer.

Model code

Characteristics

Valving systems


Brake

Installation





Options



Automatic electrical de-braking valve



Electrical de-braking valve controls braking / brake release of the hydraulic motor's static brake after "left rotation" and "right rotation" information issued from hydraulic joystick.



Electrical de-braking ports characteristics


Port	Function	ISO 1179-1 (GAZ)	ISO 11926-1 (UNF)
F	Brake pressure	G 1/4"	9/16-18 UNF-2B
1	Drain	G 3/8"	3/4-16 UNF-2B





INSTALLATION

Hydraulic motor setting

Set the pinion shaft of hydraulic motor depending on the minimum radius of the ring gear (distance A), usually indicated with a point on the ring gear by the manufacturer.



Customer's chassis recommendations



	ØU		Class	*
8	See page 7	6 x M14 x 2	12,9	230 N.m [170 lb.ft]
9	See page 7	8 x M12 x 1,75 CHC type only	12,9	145 N.m [107 lb.ft]

* : Min. values for torque and load to be transmitted



Take care over the immediate environment of the connections.

Model code

Characteristics

Valving systems

Brake


Installation

Options






OPTIONS



You can accumulate more than one optional part. Consult your Poclair Hydraulics sales engineer.


3 Brake environmental cover without plug

No plug or hole in the cover.



1 Fluorinated elastomer seals

Nitrile seals marked in the figure below replaced by fluorinated elastomer seals.



Consult your Poclair Hydraulics sales engineer.

6 Industrial support

Reduction of around 50% from the rated value in the bearings' preload value. Without external loads, increases the lifetime of the bearing support.



For a precise calculation, consult your Poclair Hydraulics application engineer.

7 Diamond™

Special treatment of the motor core which considerably increases its strength, making the motor much more tolerant to temporary instances of the operating conditions being exceeded.

Model code

Characteristics

Valving systems

Brake

Installation

Options



D Special paint or no paint

The motors are delivered with Poclain Hydraulics yellow ochre primer as standard.



Consult your Poclain Hydraulics application engineer for other colors of primer or topcoat.

H High efficiency

Reinforced piston sealing to improve volumetric efficiency.



For a precise calculation, consult your Poclain Hydraulics application engineer.

M High speed or reduced charge pressure

Option M leads to:

- In the case of MZ02: Reduction in charge pressure.
- In the case of MZE02: An increase in speed limit and a reduction in charge pressure.



For a precise calculation, consult your Poclain Hydraulics application engineer.

P Customized identification plate

Your part number can be engraved on the plate.



Consult your Poclain Hydraulics application engineer for other possibilities.



Model code

Characteristics

Valving systems

Brake

Installation

Options

Thirteen subsidiaries and a worldwide network
of more than 150 distributors and partners ...



 03/05/2013

  A40708X



Poclain Hydraulics reserves the right to make any modifications it deems necessary to the products described in this document without prior notification. The information contained in this document must be confirmed by Poclain Hydraulics before any order is submitted.

Illustrations are not binding.

The Poclain Hydraulics brand is the property of Poclain Hydraulics S.A.



 **Poclain** Driving Values for the Future

More information on

